



TM- 143

Standard Features Include:

- Up to 1MB Flash Memory and 2MB Dram Memory
- Up to 76mm (3.0") Per Second Print Speed
- Ribbon Capacity up to 300mm (964')
- Label Capacity up to 203mm OD (8.4" OD)

PRODUCT CONTROL

Take control of your products by eliminating the need for multiple labels. Create the variables as needed while determining your own quantities.

INVENTORY CONTROL

Reduce inventory by utilizing a pre-printed label template that can be applied to a variety of different products.

OVERALL CONTROL

Change products with ease and reduce waste when these changes are required.

Tags for Harsh Environments

Resists Harsh Weather Conditions

- Rain
- Snow
- Heat
- Temperatures of - 45° below 0

Resistant to Chemicals

- Oil Lubricants
- Transmission Fluid
- Anti-Freeze

Compatible with Existing Systems

- Hollander™ Power Link 1 & 2
- Pinnacle™
- Checkmate™

Color Coding Technology Available

- Color coordinate your inventory
- Find parts with ease

Pre-printed Custom Designs Available

- Add your company logo
- Web address promo & more

Compare Ultratag to Common Tyvek™ Tags
Tyvek™ Material

- Absorbs common automotive chemicals
- Imprint will often fade or smear
- Easily falls from parts

Won't Crack or Fade