

## Shrink Sleeve **SL200 Labeling System**

## **SL200 SHRINK SLEEVE LABELING SYSTEM**

## SHRINK SLEEVE APPLICATIONS

The SL200 Shrink Sleeve Label Applicator can be configured as a full body or mid body shrink sleeve label applicator by simply changing the mandrel and selecting the proper mode in the touch pad control. Features include Allen Bradley PLC Control and color touchscreen, servo driven label feed, stepper driven cutting mechanism, quick change knife plates and mandrel style sleeve handling. The system is capable of applying up to 200 tamper bands or full body sleeves per minute.

- Mandrel Style sleeve handling with sealed roller bearings
- User selectable Optical or Digital sleeve registration options
- U-Mount style mounting- compatible with most T-Base stands
- Quick change Knife Plate with disposable blades
- Integrated product detection sensor
- Color Touchscreen
- Allen-Bradley PLC
- Stepper Driven Cutter
- Full system guarding
- Encoder interface option

The SL200 can be configured for full-body, mid-body or tamper band applications up to 200 products per minute. Interchangeable mandrels and knife plates allow a wide variety of product diameters. Additional features include Allen Bradley PLC control and color touchscreen.

Speed: Up to 200 bottles per minute
Accuracy: +/- 1/32" dispensed accuracy
Other: Bottle Diameter Range: .875 – 3.86

